








NO. OF CONTACTS	A MAX	B BSC	C MAX
9	.785	.565	.400
15	.935	.715	.550
21	1.085	.865	.700
25	1.185	.965	.800
31	1.335	1.115	.950
37	1.485	1.265	1.100
51	1.435	1.215	1.050
69	1.737	1.515	1.350
100	2.170	1.800	1.442



TOLERANCE: .XXX ±.005
.XX ±.01
ANGLE ±1°

TITLE

MICRO-D METAL SHELL

SHT 1 OF 4

DWG. NO.

CMD

REV

M

CMDXXX X—X X X X X X —EMI

CRISTEK METAL SHELL
MICRO-D CONNECTORS
(MATE WITH M83513)

NUMBER OF CONTACTS
009 025 051
015 031 069
021 037 100

GENDER
P = PLUG, PIN CONTACTS
S = RECEPTACLE, SOCKET CONTACTS

HARDWARE
0 = NONE
FACTORY INSTALLED (NON-REMOVABLE)
F = FLOAT MOUNT
J = HIGH PROFILE HEX DRIVE JACKSCREW
K = HIGH PROFILE SLOTTED JACKSCREW
L = LOW PROFILE HEX DRIVE JACKSCREW *
T = THREADED INSERT
M83513 HARDWARE - FACTORY INSTALLED
2 = LOW PROFILE HEX DRIVE JACKSCREW *
3 = HIGH PROFILE HEX DRIVE JACKSCREW
5 = LOW PROFILE SLOTTED JACKSCREW *
6 = HIGH PROFILE SLOTTED JACKSCREW
7 = JACKPOST KIT *
(HARDWARE FOR SIZES 9 - 69 IS #2-56,
HARDWARE FOR SIZE 100 IS #4-40)

SHELL FINISH
A = CADMIUM
B = NICKEL
C = ANODIZE
D = CHEM FILM
E = BLACK CADMIUM
G = GOLD
P = PASSIVATION (STAINLESS STEEL)

EMI SPRINGS (PLUG ONLY)

WIRE LENGTH
STRANDED (+ 1.00 / - 0.00)
1 = 6 INCHES
2 = 12 INCHES
3 = 18 INCHES
4 = 24 INCHES
5 = 36 INCHES
6 = 72 INCHES
SOLID COPPER (+0.20 / - 0.00)
1 = 0.5 INCH
2 = 1.0 INCH
3 = 0.25 INCH

WIRE SIZE
STRANDED WIRE
0 = 26 AWG
1 = 24 AWG
2 = 28 AWG
SOLID WIRE
0 = 25 AWG
1 = 24 AWG

WIRE COLOR/TYPE
0 = WHITE STRANDED *
1 = YELLOW STRANDED
2 = 10 SOLID COLORS REPEATED *
3 = FULL COLOR CODE STRANDED
9 = SOLID COPPER *

TERMINATION
0000 - SOLDER CUP *
WIRE TYPE
STRANDED
H = HARNESS (MIL-W-16878/4)
S = SPACE (MIL-W-22759/33)
M = MILITARY (MIL-W-22759/11) *
SOLID
G = GOLD PLATED COPPER
T = TIN/LEAD PLATED COPPER

* = MOST COMMONLY USED & STOCKED WIRE TYPES AND HARDWARE OPTIONS

MATERIALS AND FINISHES ARE IAW MIL-DTL-83513 WHERE APPLICABLE
FOR DETAILS SEE MIL SPEC OR WWW.CRISTEK.COM

1. MATERIALS:

SHELL - ALUMINUM ALLOY OR STAINLESS STEEL
INSULATOR - GLASS FILLED THERMOPLASTIC
PIN/SOCKET CONTACT - COPPER ALLOY
INTERFACIAL SEAL - FLUOROSILICONE BLEND
GROUND SPRINGS - BERYLLIUM COPPER

2. FINISH:

SHELL - SEE OPTIONS ABOVE
PIN/SOCKET CONTACT - GOLD OVER NICKEL
GROUND SPRINGS - GOLD OVER NICKEL

3. SPECIFICATIONS:

CURRENT RATING ----- 3 AMPS MAX
TEMPERATURE RATING ----- -55° C TO +125° C
INSULATION RESISTANCE ----- 5000 MEGOHMS MIN
DWV AT SEA LEVEL ----- 600 VAC
DWV AT 70,000 FT ALTITUDE --- 150 VAC
CONTACT RESISTANCE:
26 AWG (STRANDED) = 28 MILLIOHMS MAX.
24 & 25 AWG (SOLID) = 25 MILLIOHMS MAX.
CONTACT RETENTION ----- 5 lb MINIMUM AXIAL LOAD
ENGAGEMENT FORCE ----- 6 oz MAX
SEPARATION FORCE ----- 0.5 oz MIN

4. ADDITIONAL INFORMATION:

DESIGN AND PERFORMANCE IN GENERAL
ACCORDANCE WITH M83513 WHERE APPLICABLE.
FOR OTHER TERMINATIONS, CONTACT CRISTEK.

TOLERANCE: .XXX ±.005
.XX ±.01
ANGLE ±1°

TITLE

MICRO-D METAL SHELL










SHT 2 OF 4

DWG. NO.










CMD

REV

M



PLUG MATING FACE



RECEPTACLE MATING FACE

TOLERANCE: .XXX ±.005
.XX ±.01
ANGLE ±1°

TITLE

MICRO-D METAL SHELL






SHT 3 OF 4

DWG. NO.

CMD

REV

M



NO. OF CONTACTS	A MAX	B BSC	C MAX	D MAX
9	.785	.565	.400	.308
15	.935	.715	.550	.308
21	1.085	.865	.700	.308
25	1.185	.965	.800	.308
31	1.335	1.115	.950	.308
37	1.485	1.265	1.100	.308
51	1.435	1.215	1.050	.351
69	1.737	1.515	1.350	.351
100	2.170	1.800	1.442	.394

EMI SPRINGS (PLUG ONLY)

TOLERANCE: .XXX ±.005
.XX ±.01
ANGLE ±1°

TITLE

MICRO-D METAL SHELL

SHT 4 OF 4

DWG. NO.

CMD

REV

M